



ZUMALIGHTING

San Clemente

Project _____

Type _____

Qty _____

Company _____

Part # _____

Overview

Specifications Housing The San Clemente post-top fixture features a heavy-duty, cast aluminum housing with a tempered glass lens. Electrical Components Zuma's high-performance LEDs leverage cutting-edge technology to enhance thermal management and ensure longevity. Each fixture is equipped with 80 CRI LEDs, with options for higher or lower CRI values available upon request. Available in Type III and Type V distributions with wide choice of color temperatures from CCT (2700K - 5000K). This fixture can be specified with Sky Night Friendly optics, designed to minimize light pollution and upward light spill. For dynamic lighting control, 0-10V dimming capabilities are available upon request. Additional control options are outlined in the specifications above. For custom integration needs, controls can be tailored to seamlessly connect with existing management systems. For more detailed information or to discuss custom solutions, please contact our sales team. This fixture can be specified with Sky Night Friendly optics, designed to minimize light pollution and upward light spill. All exterior hardware is corrosion resistant stainless steel, supplied in its natural stainless finish. Color matched hardware is available on request for select finishes; consult factory.

Lens

Impact modified and UV resistant acrylic lens with continuous operating temperature up to 80°C. Maximum transmittance of 92% (clear). Lens can be specified with optional aluminum top.

Mounting

Fixture is secured to tenon via pendant mount. Tenon top mounting options:

- Arm Mount
- Pendant Mount Mounting arms and pendant rods sold separately. Contact our sales team for more information.

Finish

Outdoor polyester powder coat, available in our Zuma standard finishes with a four-step pretreat process to ensure optimal adhesion and surface integrity. All standard finishes are provided in a fine texture with a matte sheen; additional textures and sheens are available upon request. Also available in custom RAL and in marine grade finish (MGF), specify.

Certificates & Warranty

- Designed to comply with UL 8750
- Suitable for Wet Locations
- 5-Year Warranty

Technical

- Operating Temperature: -40°F to 95°F (-40°C to 35°C)





San Clemente

Example Code: SANC-2209-15W-U-AMBR-T2-CA-SF238-BZ8-D-BAA

Item	Style	Wattage	Volts	Color Temp	Optics	Lens	Mounting	Finish	Controls	Options
SANC San Clemente	2209 22"H x 9"W	15W	U 120-277v	AMBR 560nm+	T2 Type II	CA Clear Acrylic	SF238 Fits over 2-3/8" OD tenon	BZ8 Zuma Bronze	D Dimming 0-10v	BAA Buy American Act Compliant
	3716 37"H x 16"W	30W	HV 347-480v	27K 2700K	T3 Type III	FA Frosted Acrylic	SF300 Fits over 3" OD tenon	BK GT Black	PC Photocell	BABA Build America, Buy America Act Compliant
		55W		3K 3000K	T4 Type IV	OA Opal White Acrylic	WM Wall Mount	SL Iridium Silver	M Motion Sensor	MGF Marine Grade Finish
		85W		35K 3500K	T5 Type V			WH Alpine White		SKY Sky Night Friendly
		100W		4K 4000K				GR2 Midnight Gray		S Surge Protection
		130W		45K 4500K				GRN Moss Green		HSS House Side Shield
		155W		5K 5000K				CCxxx ¹ Custom Color		
		185W								

1 Custom colors: Available in smooth and textured finishes. Also available in RAL and Sherwin Williams colors, consult factory.



San Clemente

Dimensions

