

Stealth Pole Mount

Overview

Specifications Housing The Stealth pole mount fixture is fabricated from a combination of extruded, cast and formed aluminum alloys. Electrical Components Zuma's high-performance LEDs leverage cutting-edge technology to enhance thermal management and ensure longevity. Each fixture is equipped with 80 CRI LEDs, with options for higher or lower CRI values available upon request. Available in Type II, III, IV, and V distributions with wide choice of color temperatures from CCT (2700K - 5000K). These LEDs are designed to fit LEDIL lenses with IP67 rating. This fixture can be specified with Sky Night Friendly optics, designed to minimize light pollution and upward light spill. For dynamic lighting control, 0-10V dimming capabilities are available upon request. Additional control options are outlined in the specifications above. For custom integration needs, controls can be tailored to seamlessly connect with existing management systems. For more detailed information or to discuss custom solutions, please contact our sales team. All exterior hardware is corrosion resistant stainless steel, supplied in its natural stainless finish. Color matched hardware is available on request for select finishes; consult factory.

Lens

Optional anti-glare diffusion lens available, fabricated from acrylic and can be specified frosted or opal, flat or convex. Fixtures specified without diffusion lens are equipped with exposed optical lens.

Mounting

Side arm mount.

Finish

Outdoor polyester powder coat, available in our Zuma standard finishes with a four-step pretreat process to ensure optimal adhesion and surface integrity. All standard finishes are provided in a fine texture with a matte sheen; additional textures and sheens are available upon request. Also available in custom RAL and in marine grade finish (MGF), specify.

Certificates & Warranty

- Designed to comply with UL 8750
- Suitable for Wet Locations
- 5-Year Warranty

Technical

- Operating Temperature: -40°F to 95°F (-40°C to 35°C)





ZUMALIGHTING

Project _____ Type _____ Qty _____

Company _____ Part # _____

Stealth Pole Mount

Example Code: STH-PM-20W-U-AMBR-T2-NL-SAM-BZ8-D-BAA


Item	Wattage	Volts	Color Temp	Optics	Lens	Mounting	Finish	Controls	Options
STH-PM Stealth Pole Mount	20W 1960-2260	U 120-277v	AMBR 560nm+	T2 Type II	NL No Diffusion Lens	SAM Side Arm Mount	BZ8 Zuma Bronze	D Dimming 0-10v	BAA Buy American Act Compliant
	30W 2940-3390	HV 347-480v	27K 2700K	T3 Type III	FDL Anti-Glare Frosted Diffusion		BK GT Black	M Motion Sensor	BABA Build America, Buy America Act Compliant
	40W 2940-4520		3K 3000K	T4 Type IV	ODL Anti-Glare Opal Diffusion		SL Iridium Silver		MGF Marine Grade Finish
	60W 5880-6780		35K 3500K	T5 Type V			WH Alpine White		SKY Sky Night Friendly
	80W 7840-9040		4K 4000K				GR2 Midnight Gray		HSS Houseside Shield
	90W 8820-10170		45K 4500K				GRN Moss Green		S Surge Protection
	120W 11760-13560		5K 5000K				CCxxx¹ Custom Color		
	150W 14700-16950								
	160W 15880-18080								

1 Custom colors: Available in smooth and textured finishes. Also available in RAL and Sherwin Williams colors, consult factory.



Stealth Pole Mount

Dimensions



HOLES PATTERN

