



San Clemente

Specifications

Housing

The San Clemente post-top fixture features a heavy-duty, cast aluminum housing with a tempered glass lens.

Electrical Components

Zuma's high-performance LEDs leverage cutting-edge technology to enhance thermal management and ensure longevity. Each fixture is equipped with 80 CRI LEDs, with options for higher or lower CRI values available upon request. Available in Type III and Type V distributions with wide choice of color temperatures from CCT (2700K - 5000K). This fixture can be specified with Sky Night Friendly optics, designed to minimize light pollution and upward light spill.

For dynamic lighting control, 0-10V dimming capabilities are available upon request. Additional control options are outlined in the specifications above. For custom integration needs, controls can be tailored to seamlessly connect with existing management systems. For more detailed information or to discuss custom solutions, please contact our sales team. This fixture can be specified with Sky Night Friendly optics, designed to minimize light pollution and upward light spill.

Mounting

Fixture is secured to tenon via pendant mount. Tenon top mounting options:

- Arm Mount
- Pendant Mount

Mounting arms and pendant rods sold separately. Contact our sales team for more information.

Lens

Impact modified and UV resistant acrylic lens with continuous operating temperature up to 80°C. Maximum transmittance of 92% (clear). Lens can be specified with optional aluminum top.

Finish

Our thermoset polyester powder coats, available in standard and custom colors, undergo rigorous preparation including sandblast treatment to ensure optimal adhesion and surface integrity. Marine grade finish available upon request.

Each coating is meticulously applied to achieve a uniform thickness of 3-5 mil, then oven-baked to enhance durability and color stability. This process guarantees a superior finish that withstands the elements and maintains its aesthetic appeal over time. For specific color requirements or further details on our finishing process, please contact our customer support team.



Certificates & Warranty

- Designed to comply with UL 8750
- Suitable for Wet Locations
- 5-Year Warranty

Technical

- Operating Temperature: -40°F to 95°F (-40°C to 35°C)





ZUMALIGHTING

Project _____

Type _____

Qty _____

Company _____

Part # _____

San Clemente

Item	Size	Wattage	Volts	Color Temp	Optics	Lens	Mounting	Finish	Options
SANC San Clemente	2411 24"H x 11"W	15W	U 120v-277v	AMBR¹ 560nm+	T2 Type II	CA Clear Acrylic	SF238 Fits over 2-3/8" OD tenon	BZ8 Zuma Bronze	BAA² Buy American Act Compliant
	3015 30"H x 15"W	30W	HV 347v-480v	27K 2,700K	T3 Type III	FA Frosted Acrylic	SF300 Fits over 3" OD tenon	BK GT Black	BABA² Build America, Buy America Act Compliant
	3619 36"H x 19"W	55W		3K 3,000K	T4 Type IV	OA Opal White Acrylic	WM Wall Mount	SL Iridium Silver	MGF Marine Grade Finish
		85W		35K 3,500K	T5 Type V			WH Alpine White	D Dimming (0-10v)
		100W		4K 4,000K				GRY Granite Gray	SKY³ Sky Night Friendly
		130W		45K 4,500K				GRN Moss Green	PC Photocell
		155W		5K 5000K				CC Custom (Specify RAL)	M Motion Sensor
		185W							S Surge Protection
									HSS House Side Shield

1 Amber lighting is above 560nm for turtle and wildlife friendly requirements
2 Consult our sales team for detailed information on compliance with domestic manufacturing regulations.
3 Only available with select optics. Consult our sales team for details.





San Clemente

Dimensions



Model	A	B
SANC-10	24"	11"
SANC-20	30"	15"
SANC-30	36"	19"

