



ZUMALIGHTING

Project _____

Type _____

Qty _____

Company _____

Part # _____

Stealth Direct Wall Mount

Overview

Specifications Housing The Stealth direct wall mount fixture is fabricated from a combination of extruded, cast and formed aluminum alloys. Electrical Components Zuma's high-performance LEDs leverage cutting-edge technology to enhance thermal management and ensure longevity. Each fixture is equipped with 80 CRI LEDs, with options for higher or lower CRI values available upon request. Available in Type II, III, IV and V distributions with wide choice of color temperatures from CCT (2700K - 5000K). These LEDs are designed to fit LEDIL lenses with IP67 rating. This fixture can be specified with Sky Night Friendly optics, designed to minimize light pollution and upward light spill. For dynamic lighting control, 0-10V dimming capabilities are available upon request. Additional control options are outlined in the specifications above. For custom integration needs, controls can be tailored to seamlessly connect with existing management systems. For more detailed information or to discuss custom solutions, please contact our sales team. All exterior hardware is corrosion resistant stainless steel, supplied in its natural stainless finish. Color matched hardware is available on request for select finishes; consult factory.

Lens

Optional anti-glare diffusion lens available, fabricated from acrylic and can be specified frosted or opal, flat or convex. Fixtures specified without diffusion lens are equipped with exposed optical lens.

Mounting

Mounting options:

- Wall Mount Fixture can also be installed on mounting arms, sold separately. Contact our sales team for more information.

Finish

Outdoor polyester powder coat, available in our Zuma standard finishes with a four-step pretreat process to ensure optimal adhesion and surface integrity. All standard finishes are provided in a fine texture with a matte sheen; additional textures and sheens are available upon request. Also available in custom RAL and in marine grade finish (MGF), specify.

Certificates & Warranty

- Designed to comply with UL 8750
- Suitable for Wet Locations
- 5-Year Warranty

Technical

- Operating Temperature: -40°F to 95°F (-40°C to 35°C)





ZUMALIGHTING

Project _____ Type _____ Qty _____

Company _____ Part # _____

Stealth Direct Wall Mount

Example Code: STH-DWM-7W-U-AMBR-T2-NL-WM-BZ8-D-BAA

Item	Wattage	Volts	Color Temp	Optics	Lens	Mounting	Finish	Controls	Options
STH-DWM Stealth Direct Wall Mount	7W 688-805	U 120-277v	AMBR 560nm+	T2 Type II	NL No Diffusion Lens	WM Wall Mount	BZ8 Zuma Bronze	D Dimming 0-10v	BAA Buy American Act Compliant
	10W 980-1159	HV 347-480v	27K 2700K	T3 Type III	FDL Anti-Glare Frosted Diffusion		BK GT Black	M Motion Sensor	BABA Build America, Buy America Act Compliant
	12W 1186-1380		3K 3000K	T4 Type IV	ODL Anti-Glare Opal Diffusion		SL Iridium Silver		MGF Marine Grade Finish
	15W 1470-1725		35K 3500K	T5 Type V			WH Alpine White		SKY Sky Night Friendly
	20W 1960-2300		4K 4000K				GR2 Midnight Gray		HSS Houseside Shield
	25W 2450-2875		45K 4500K				GRN Moss Green		S Surge Protection
	30W 2940-3450		5K 5000K				CCxxx¹ Custom Color		

1 Custom colors: Available in smooth and textured finishes. Also available in RAL and Sherwin Williams colors, consult factory.

2 Product specifications and design subject to change, at any time, without notice.



Please consult Zuma Lighting for the most current information.

Rev 100926

Stealth Direct Wall Mount

Dimensions

