



ZUMALIGHTING

Project _____

Type _____

Qty _____

Company _____

Part # _____

Presidential Pole

Overview

Specifications One-Piece Aluminum Pole Zuma's One Piece Pole Series consists of a cast aluminum, structural base welded to a high grade aluminum shaft (pg.2 for shaft options). Overall pole height is measured from the bottom of the base to the pole top. Note: tenon height not included in specified pole height. Handhole / Grounding Reinforced hand hole is furnished with cover. All fasteners are stainless steel. All poles include internal ground lug / nut welded to the pole within handhole. Baseplate Baseplate size and bolt circle vary based on product (see pg.3). All exterior hardware is corrosion resistant stainless steel, supplied in its natural stainless finish. Color matched hardware is available on request for select finishes; consult factory.

Mounting

Specify drill pattern & configuration or select tenon option. Anchorbolts Anchorbolts are equipped with (2) galvanized nuts and (2) washers per bolt, size and length vary based on selected pole size. All anchorbolts are hot dip galvanized carbon steel with minimum yield strength of 50,000 psi. Pole Top Cap Standard drill-mount poles include black removable top cap. Powder Coat Finish Thermoset polyester powder coats undergo sandblast treatment to ensure optimal adhesion and surface integrity. Each coating is meticulously applied to achieve a uniform thickness of 2-4 mils. Galvanized and marine grade finish can be specified.

Finish

Outdoor polyester powder coat, available in our Zuma standard finishes with a four-step pretreat process to ensure optimal adhesion and surface integrity. All standard finishes are provided in a fine texture with a matte sheen; additional textures and sheens are available upon request. Also available in custom RAL and in marine grade finish (MGF), specify.

Certificates & Warranty

- Designed to comply with UL 8750
- Suitable for Wet Locations
- 5-Year Warranty

Technical

- Operating Temperature: -40°F to 95°F (-40°C to 35°C)





ZUMALIGHTING

Project _____ Type _____ Qty _____

Company _____ Part # _____

Presidential Pole

Example Code: P-Pres-10-4R-F-120-BC912-XM-BZ8-GFIP

Item	Height	Pole-Size	Shaft	Wall-Thickness	Bolt-Circle	Mounting	Finish	Options
P-Pres Presidential Pole	10	4R 4" Round Straight	F Fluted	120 .120 in	BC912 9 1/2" dia.	XM No drilling, no tenon	BZ8 Zuma Bronze	GFIP provision only
	12	5R 5" Round Straight	NF Non-Fluted	188 .188 in	BC1105 11 1/2" dia.	S1 Single Drilling	BK GT Black	MGF Marine Grade Finish
	15	6R 6" Round Straight		250 .25 in	CBP Custom Bolt Pattern	D180 Double 180° Drilling	SL Iridium Silver	EYE Eyebolt (specify location)
	20	4RT 4" Round Tapered				D90 Double 90° Drilling	WH Alpine White	BAA Buy American Act Compliant
	25	5RT 5" Round Tapered				T90 Triple Drilling	GR2 Midnight Gray	BABA Build America, Buy America Act Compliant
	CH Custom Height	6RT 6" Round Tapered				Q90 Quad Drilling	GRN Moss Green	LAB Less Anchor Bolts
						TN3 3" OD x 4" length	CCxxx¹ Custom Color	CSTP Custom Provision
						TN238 2-3/8" OD x 4" length		VD Vibration Dampener
						TNC Custom Tenon		

1 Custom colors: Available in smooth and textured finishes. Also available in RAL and Sherwin Williams colors, consult factory.



Presidential Pole

Dimensions

Presidential 17.500" Base Template

