

Silo Bollard

Overview

The Silo Bollard is constructed from a combination of case and fabricated aluminum. Designed to illuminate pathways, it also enhances safety by clearly defining property boundaries for drivers.

Size

Available in standard 9" diameter with standard height of 9". Custom sizes available.

Electrical

- Watts: 7, 10, 12, and 15W.
- Voltage: 120v through 277v (U). 347-480v (HV).

LED

High performance LED CRI: 80. Color temperature ranges from CCT: 2700K - 5000K. Also available in Amber LED array.

Lens

Acrylic Lens: Frosted Lens (FL), Opal White Lens (OL), or Clear Lens (CL).

Mounting

Heavy duty internal baseplate (IBP) installs on the ground with anchor bolts (four anchor bolts, nuts and washers).

Finish

Outdoor polyester powder coat, available in our Zuma standard finishes with a four-step pretreat process to ensure optimal adhesion and surface integrity. Also available in custom RAL and in marine grade finish (MGF), specify.

Controls

- Dimming: 0-10v dimming (D) available.
- Photocell: Small button Style photo cell available in 120V (PH1)¹ or 120v through 277v (PH2) on side of fixture².

- 1 For use with 120v input voltage only.
2 For use with 120v through 277v universal voltage (U) only.

Options

- Bollard can be made to "Buy American Compliant" (BAA)¹ and "Build America, Buy America Act Compliant" (BABA)¹ (includes BAA)
- Emergency Battery Backup (EMB)
- Surge Protection (S): Field installed in the bottom of the bollard.
- Marine grade finish (MGF) available in standard and custom colors, consult factory.
- Vandal Resistance Hardware (VRH): Optional vandal resistant stainless steel hardware installed for added security.

- 1 Must specify at time of ordering in order to ensure product is manufactured to meet all required compliances.



Certificates & Warranty

- Designed to comply with UL 8750
- Suitable for Wet Locations
- 5-Year Warranty

Technical

- Operating Temperature: -40°F to 95°F (-40°C to 35°C)





ZUMALIGHTING

Project _____ Type _____ Qty _____

Company _____ Part # _____

Silo Bollard

Example Code: SIL-B-15W-U-35K-CL-IBP-GRY-D-PC-BAA-EMB-S-MGF-VRH

Item	Wattage	Volts	Color Temp	Lens	Mounting	Finish	Controls	Options
SIL-B Silo Bollard	7W	U 120v-277v	27K 2700K	FL Frosted Lens	IBP Internal Baseplate	BZ8 Zuma Bronze	D Dimming (0-10v)	BAA ¹ Buy American Act Compliant
	10W		3K 3000K	OL Opal White Lens		BK GT Black	PC Photocell	BABA ¹ Build America, Buy America Act Compliant
	12W		35K 3500K	CL Clear Lens		SL Iridium Silver		EMB Emergency Battery Backup
	20W		4K 4000K			WH Alpine White		S Surge Protection
	25W		45K 4500K			GRY Granite Gray		MGF Marine Grade Finish
	30W		5K 5000K			GRN Moss Green		VRH Vandal Resistant Hardware
	40W		AMBR ² 560nm+			CCxxx ³ Custom Color		

1 Consult our sales team for detailed information on compliance with domestic manufacturing regulations.
2 Amber lighting is for turtle and wildlife friendly requirements (560nm+) and lumen outputs will be reduced to approximately 40-50 lm/w.
3 Custom colors: Available in smooth and textured finishes. Also available in RAL and Sherwin Williams colors, consult factory.



Silo Bollard

Dimensions

