

Irvine Bollard

Overview

The Irvine bollard shaft is constructed from extruded aluminum tubing. Bollard head is constructed from a combination of cast and fabricated aluminum. Designed to illuminate pathways, it also enhances safety by clearly defining property boundaries for drivers. All exterior hardware is corrosion resistant stainless steel, supplied in its natural stainless finish. Color matched hardware is available on request for select finishes; consult factory.

Size

Available in standard 6" and 8" square size with standard heights (30", 36", 42" and 48"). Custom size available.

Electrical

- Watts: 7, 10, 12, 15 and 20W
- Voltage: 120v through 277v (U). 347-480v (HV).

LED

High performance LED CRI: 80. Color temperature ranges from CCT: 2700K - 5000K. Also available in Amber LED array.

Optics

Available Optics: Type II (T2), Type III (T3), Type IV (T4), and Type V (T5).

Mounting

Heavy duty internal baseplate (IBP) installs on the ground with anchor bolts (four anchor bolts, nuts and washers). External base plate (ESM) also available, consult factory.

Finish

Outdoor polyester powder coat, available in our Zuma standard finishes with a four-step pretreat process to ensure optimal adhesion and surface integrity. All standard finishes are provided in a fine texture with a matte sheen; additional textures and sheens are available upon request. Also available in custom RAL and in marine grade finish (MGF), specify.

Controls

- Dimming: 0-10v dimming (D) available.
- Photocell: Small button style photocell available in 120v-277v on side of fixture (PC).
- Motion Sensor (M)

Options

- Bollard can be made to "Buy American Compliant" (BAA)¹ and "Build America, Buy America Act Compliant" (BABA)¹ (includes BAA)
- Emergency Battery Backup (EMB)
- Sky Night Friendly (SKY)
- 180° Houseside Shield on Optics (HSSOP)
- Surge Protection (S): Field installed in the bottom of the bollard.
- Marine grade finish (MGF) available in standard and custom colors, consult factory.
- Vandal Resistance Hardware (VRH): Optional vandal resistant stainless steel hardware installed for added security. ¹



Certificates & Warranty

- Designed to comply with UL 8750
- Suitable for Wet Locations
- 5-Year Warranty

Technical

- Operating Temperature: -40°F to 95°F (-40°C to 35°C)



Project _____

Type _____

Qty _____

Company _____

Part # _____

Irvine Bollard

Example Code: IRA-B-0630-10W-U-27K-T2-IBP-BZ8-D-BAA

Item	Size	Wattage	Volts	Color Temp	Optics	Mounting	Finish	Controls	Options
IRA-B Irvine Bollard	0630 6" Dia. x 30" H	10W	U 120-277v	27K 2700K	T2 Type II	IBP Internal Baseplate (Std.)	BZ8 Zuma Bronze	D Dimming 0-10v	BAA Buy American Act Compliant
	0636 6" Dia. x 36" H	12W	HV 347-480v	3K 3000K	T3 Type III	ESM External Surface Mount	BK GT Black	PC Photocell	BABA Build America, Buy America Act Compliant
	0642 6" Dia. x 42" H	15W		35K 3500K	T4 Type IV		SL Iridium Silver	M Motion Sensor	EMB Emergency Battery Backup
	0648 6" Dia. x 48" H	20W		4K 4000K	T5 Type V		WH Alpine White	SKY Sky Night Friendly	HSSOP 180° Houseside Shield (Optics)
	0830 8" Dia. x 30" H	30W		45K 4500K			GR2 Midnight Gray		S Surge Protection
	0836 8" Dia. x 36" H			5K 5000K			GRN Moss Green		MGF Marine Grade Finish
	0842 8" Dia. x 42" H			AMBR 560nm+			CCxxx¹ Custom Color		VRH Vandal Resistant Hardware
	0848 8" Dia. x 48" H								
	CSxxx Custom Size								

1 Custom colors: Available in smooth and textured finishes. Also available in RAL and Sherwin Williams colors, consult factory.



Irvine Bollard

Dimensions

