



Holmby

Specifications

Housing

The Holmby architectural street lamp features a cast-aluminum fitter with an acrylic acorn style lens with optional aluminum top.

Electrical Components

Zuma's high-performance LEDs leverage cutting-edge technology to enhance thermal management and ensure longevity. Each fixture is equipped with 80 CRI LEDs, with options for higher or lower CRI values available upon request. Available in Type III and Type V distributions with wide choice of color temperatures from CCT (2700K - 5000K).

For dynamic lighting control, 0-10V dimming capabilities are available upon request. Additional control options are outlined in the specifications above. For custom integration needs, controls can be tailored to seamlessly connect with existing management systems. For more detailed information or to discuss custom solutions, please contact our sales team. This fixture can be specified with Sky Night Friendly optics, designed to minimize light pollution and upward light spill.

Mounting

Fixture is secured to tenon via pendant mount. Tenon top mounting options:

- Arm Mount
- Pendant Mount

Mounting arms and pendant rods sold separately. Contact our sales team for more information.

Lens

Impact modified and UV resistant acrylic lens with continuous operating temperature up to 80°C. Maximum transmittance of 92% (clear). Lens can be specified with optional aluminum top.

Finish

Our thermoset polyester powder coats, available in standard and custom colors, undergo rigorous preparation including sandblast treatment to ensure optimal adhesion and surface integrity. Marine grade finish available upon request.

Each coating is meticulously applied to achieve a uniform thickness of 3-5 mil, then oven-baked to enhance durability and color stability. This process guarantees a superior finish that withstands the elements and maintains its aesthetic appeal over time. For specific color requirements or further details on our finishing process, please contact our customer support team.



Certificates & Warranty

- Designed to comply with UL 8750
- Suitable for Wet Locations
- 5-Year Warranty

Technical

- Operating Temperature: -40°F to 95°F (-40°C to 35°C)



Holmby

Item	Wattage ¹	Volts	Color Temp	Optics	Mounting	Finish	Options	Design Options
HMB Holmby	15W	U 120v-277v	AMBR² 560nm+	T3 Type III	SF300 Fits over 3" OD tenon	BZ8 Zuma Bronze	BAA³ Buy American Act Compliant	ALT Aluminum Top
	30W	HV 347v-480v	27K 2,700K	T5 Type V		BK GT Black	BABA³ Build America, Buy America Act Compliant (Includes BAA)	F Finial
	55W		3K 3,000K			SL Iridium Silver	MGF Marine Grade Finish	NC No Caged Housing
	85W		35K 3,500K			WH Alpine White	D Dimming (0-10v)	
	100W		4K 4,000K			GRY Granite Gray	SKY⁴ Sky Night Friendly	
	130W		45K 4,500K			GRN Moss Green	PC Photocell	
	155W		5K 5000K			CC Custom (Specify RAL)	M Motion Sensor	
	185W						S Surge Protection	
						HSS House Side Shield		

1 Lumen values are approximate and may vary based on factors such as distribution type and color temp
 2 Amber lighting is above 560nm for turtle and wildlife friendly requirements
 3 Consult our sales team for detailed information on compliance with domestic manufacturing regulations.
 4 Only available with select optics. Consult our sales team for details.





Holmby

Dimensions

