



**ZUMALIGHTING**

Project \_\_\_\_\_

Type \_\_\_\_\_

Qty \_\_\_\_\_

Company \_\_\_\_\_

Part # \_\_\_\_\_

# Chelsea

## Construction

The Chelsea architectural fixture is fabricated from heavy duty cast aluminum and extruded aluminum base with an outdoor polyester powder coat finish.



## Electrical Components

- Watts : 20w through 120w, Custom watts available, consult factory.
- Voltage: 120v through 277v and High voltage 347V - 480V.

## LED

High performance LED CRI: 80. Color temperature ranges from CCT: 2700K - 5000K. Also available in Amber +560nm (AMBR).

## Optic

Type II (T2), Type III (T3), Type IV (T4), and Type V (T5)

## Mounting

- Designed to fit over a 3" O.D. x 4" L Tenon (SF300),

## Finish

Outdoor polyester powder coat, available in our Zuma standard finishes with a four-step pretreat process to ensure optimal adhesion and surface integrity. Also available in custom RAL and in marine grade finish (MGF), specify.



## Controls

- Dimming: 0-10v dimming (D) available.
- Photocell: Mounts to top of fixture (SAM) or side (TAM)
- Motion Sensor (M)

## Options

- Chelsea can be made to "Buy American Compliant" (BAA) and "Build America, Buy America Act Compliant" (BABA) (includes BAA)
- SKY = Sky Night Friendly: Downward light only.
- HSS = 180° House Side Shield.
- HSSOP = 180° Houseside Shield (Optics)
- Super Durable Marine Grade Finish (MGF) available in standard and custom colors, consult factory.
- SP = Surge Protection: To be field installed in the bottom of the pole.

## Certificates & Warranty

- Designed to comply with UL 8750
- Suitable for Wet Locations
- 5-Year Warranty

## Technical

- Operating Temperature: -40°F to 95°F (-40°C to 35°C)



# Chelsea

Item	Wattage	Volts	Color Temp	Optics	Mounting	Finish	Controls	Options
CHE Chelsea	20W	U 120v-277v	27K 2700K	T2 Type II	SF300 Fits over 3" OD tenon	BZ8 Zuma Bronze	D Dimming 0-10v	BAA <sup>1</sup> Buy American Act Compliant
	30W	HV 347v-480v	3K 3000K	T3 Type III		BK GT Black	PC Photocell	BABA <sup>1</sup> Build America, Buy America Act Compliant (Includes BAA)
	40W		35K 3500K	T4 Type IV		SL Iridium Silver	M Motion Sensor	SKY Sky Night Friendly
	50W		4K 4000K	T5 Type V		WH Alpine White		HSS 180° Houseside Shield
	60W		45K 4500K			GRY Granite Gray		HSSOP 180° Houseside Shield (Optics)
	80W		5K 5000K			GRN Moss Green		MGF Marine Grade Finish
	100W		AMBR <sup>2</sup> 560nm+			CCxxx <sup>3</sup> Custom Color		SP Surge Protection
	120W							

1 Consult our sales team for detailed information on compliance with domestic manufacturing regulations.  
2 Amber lighting is for turtle and wildlife friendly requirements (560nm+) and lumen outputs will be reduced to approximately 40-50 lm/w.  
3 Custom colors: Available in smooth and textured finishes. Also available in RAL and Sherwin Williams colors, consult factory.

# Chelsea

## Dimensions

