

**ZUMA**LIGHTING

Project _____ Type _____ Qty _____

Company _____ Part # _____

Presidential Pole

Specifications



One-Piece Aluminum Pole

Zuma's One Piece Pole Series consists of a cast aluminum, structural base welded to a high grade aluminum shaft (pg.2 for shaft options). Overall pole height is measured from the bottom of the base to the pole top. Note: tenon height not included in specified pole height.

Handhole / Grounding

Reinforced hand hole is furnished with cover. All fasteners are stainless steel. All poles include internal ground lug / nut welded to the pole within handhole.

Baseplate

Baseplate size and bolt circle vary based on product (see pg.3).

Mounting

Specify drill pattern & configuration or select tenon option.

Anchorbolts

Anchorbolts are equipped with (2) galvanized nuts and (2) washers per bolt, size and length vary based on selected pole size. All anchorbolts are hot dip galvanized carbon steel with minimum yield strength of 50,000 psi.

Pole Top Cap

Standard drill-mount poles include black removable top cap.

Powder Coat Finish

Thermoset polyester powder coats undergo sandblast treatment to ensure optimal adhesion and surface integrity. Each coating is meticulously applied to achieve a uniform thickness of 2-4 mils. Galvanized and marine grade finish can be specified.





ZUMA LIGHTING

Project _____ Type _____ Qty _____

Company _____ Part # _____

Presidential Pole

Item	Height (ft)	Pole Size	Shaft	Wall Thickness	Bolt Circle ¹	Mounting ²	Finish	Options
P-PRES Presidential One-piece Pole	10	4R 4" Round Straight	F Fluted	120 .120 in	BC912 9 1/2" dia.	XM No drilling, no tenon	BZ8 Zuma Bronze	GFIP GFIP (provision only)
	12	5R 5" Round Straight	NF Non-Fluted	188 .188 in	BC1105 11 1/2" dia.	S1 Single Drilling	BK GT Black	MGF Marine Grade Finish
	15	6R 6" Round Straight		250 .25 in	CBP Custom Bolt Pattern	D180 Double 180° Drilling	SL Iridium Silver	EYE Eyebolt (specify location)
	20	4RT 4" Round Tapered				D90 Double 90° Drilling	WH Alpine White	BAA³ Buy America Act Compliant
	25	5RT 5" Round Tapered				T90 Triple Drilling	GRY Granite Gray	BABA³ Build America, Buy America Compliant
CH Custom Height		6RT 6" Round Tapered				Q90 Quad Drilling	GRN Moss Green	LAB Less Anchor Bolts
						TN3 3" OD x 4" length	CC Custom	CSTP Custom Provision
						TN238 2-3/8" OD x 4" length		VD Vibration Dampener
						TNC Custom Tenon		

1 Smaller baseplate sizes are available only for select pole sizes.
Please refer to product specifications or contact us for compatibility details.

2 Standard drill location for fixture mounting is 2" below top of pole.
Reference page 5 for specific mounting options.

3 Consult our sales team for detailed information on compliance with domestic
manufacturing regulations.





ZUMA LIGHTING

Project _____ Type _____ Qty _____

Company _____ Part # _____

Presidential Pole

Presidential 17.500" Base Template

Dimensions

