



ZUMALIGHTING
QUALITY OUTDOOR SOLUTIONS



MODEL
BEELINE

TYPE
LED

SERIES
COLUMNS



ZUMA LIGHTING LLC
325 N LARCHMONT BLVD STE 406, LOS ANGELES, CA 90004
INFO@ZUMALIGHTING.COM • (310) 975-3126 • ZUMALIGHTING.COM

ORDERING INFORMATION

FIXTURE	SHAFT HEIGHT	HEAD LENGTH	SOURCE	VOLTS	CCT	OPTICS
BEE-C = Beeline Column	10 = 10ft 12 = 12ft 15 = 15ft CH = Custom Height	6416 = 16"L 6424 = 24"L 6432 = 32"L 6440 = 40"L CL = Custom Length	23W = 2300lm - 2700lm 40W = 4180lm - 4620lm 50W = 5300lm - 5750lm 62W = 6500lm - 7100lm 80W = 8350lm - 9150lm 100W = 10450lm - 11050lm 120W = 12540lm - 13860lm <i>Contact sales for additional options</i>	U = 120v-277v CV = Custom Voltage	27K = 27000K 3K = 3000K 35K = 3500K 4K = 4000K 45K = 4500K 5K = 5000K	T2 = Type II T3 = Type III T4 = Type IV T5 = Type V
CONFIG	COLOR	OPTIONS				
S1 = Single Head D180 = Double 180° Heads D90 = Double 90° Heads T90 = Triple Heads Q90 = Quad Heads	BZ8 = Zuma Bronze BK = GT Black WH = Alpine White SL = Iridium Silver GRY = Granite Gray GRN = Moss Green CC = Custom <i>Specify RAL</i>	M = Motion Sensor D = 0-10v Dimming SP = Surge Protection PC = Photocell MGF = Marine Grade Finish HSS = House-side Shield BAA = Buy American Act Compliant				

SPECIFICATIONS

Housing & Shaft

The Beeline series housing is an ETL listed weather tight 2-piece aluminum extrusion unit. Shaft is fabricated from either extruded aluminum or carbon steel.

LED

High performance LEDs utilize state-of-the-art technologies for improved thermal performance. Available in Types II, III, IV, & V with wide choice of color temperatures ranging from CCT (2700K - 6500K). These LEDs are designed to fit LEDIL lenses with IP67 rating.

Mounting Options

Heavy duty aluminum base plate secures to the housing. Mounting kit with (4) 3/4" x 24" x 3" anchor bolts, included. See installation instructions .pdf for details.



Finish

Thermoset polyester oven-baked powder coat, in any standard color. Custom colors are available to your specification. Marine grade finish available upon request.

Certificates & Warranty

- Buy American Act (BAA) Compliant
- ETL Listed
- IP65 Tested
- Suitable for Wet Locations
- 5-Year Warranty

Dimensions

