



ZUMALIGHTING
QUALITY OUTDOOR SOLUTIONS



MODEL
BRENTWOOD

TYPE
LED

SERIES
ARCHITECTURAL

ZUMA LIGHTING LLC
325 N LARCHMONT BLVD STE 406, LOS ANGELES, CA 90004
INFO@ZUMALIGHTING.COM • (310) 975-3126 • ZUMALIGHTING.COM

ORDERING INFORMATION



BRE with optional opal white acrylic lens and optional copper shade

Model BRENTWOOD
Type LED
Series ARCHITECTURAL

FIXTURE	WATTAGE	VOLTS	COLOR TEMP	OPTICS	MOUNT	LENS	COLOR	OPTIONS
BRE	13W = 2080lm to 2200lm 20W = 2400lm to 3150lm 30W = 4050lm to 4400lm 40W = 5800lm to 6300lm	U = 120v-277v 8 = 480v	27K = 2700K 3K = 3000K 35K = 3500K 4K = 4000K 5K = 5000K	T5 = 360°	I = post top A = ●—● B = ●—●—● C = ●—● D = ●—●—● E = ●—● F = ●—●—● G = ●—● (wall mount)	FA = Frosted Acrylic OA = Opal White Acrylic	DB = Dark Bronze BK = Black WH = White SL = Silver CC = Custom	M = Motion Sensor PC = Photocell D = Dimming S = Surge Protection LS = 180° Cutoff Shield CS = Copper Shade

ZUMA LIGHTING LLC

325 N LARCHMONT BLVD STE 406, LOS ANGELES, CA 90004

INFO@ZUMALIGHTING.COM • (310) 975-3126 • ZUMALIGHTING.COM

SPECIFICATIONS

Housing

The fixture housing is constructed from a combination of fabricated, cast, and spun aluminum.

Electrical Components

High performance LEDs utilize state-of-the-art technologies for improved thermal performance. Available with Type V 360° distribution pattern w/ optional 180° cutoff shield. Color temperatures range from CCT (2700K – 6500K). These LEDs are designed to fit LEDIL lenses with IP67 rating.

Lens

Acrylic lens available in frosted or opal.

Finish

Thermoset polyester oven-baked powder coat, in any standard color. Custom colors are available to your specification. Marine grade finish available upon request.

Certificates & Warranty

- ETL Listed
- Suitable for Wet Locations
- 5-Year Warranty

Mounting

Fixture can be installed on post-top.

Tenon top mounting options:

- over 3" OD (standard)

Fixture can also be installed on mounting arms, sold separately. See architectural arm .pdf for style options.

Dimensions

