



ZUMALIGHTING
QUALITY OUTDOOR SOLUTIONS



MODEL
DURBAN

TYPE
LED COLUMN

SERIES
ARCHITECTURAL

ZUMA LIGHTING LLC
325 N LARCHMONT BLVD STE 406, LOS ANGELES, CA 90004
INFO@ZUMALIGHTING.COM • (310) 975-3126 • ZUMALIGHTING.COM

ORDERING INFORMATION

Model Durban
Type LED COLUMN
Series Architectural



FIXTURE	SIZE	SOURCE	VOLTS	LAMP / TEMP	COLOR	LENS	OPTIONS
DUR-C (Column)	12 = 12' length 15 = 15' length	10W 20W 30W 40W 50W 60W 70W 80W 90W 100W 120W <i>Column wattages available 10W - 120W</i>	U = 120v- 277v 8 = 480v	3K = 3000K 4K = 4000K 5K = 5000K	DB = Dark Bronze BK = Black WH = White SL = Silver CC = Custom	FA = Frosted Acrylic OA = Opal Acrylic	SP = Surge Protection SLED= Static Color LED* CLED = Color Changing LED* <i>*Consult factory for color LED options</i>

SPECIFICATIONS

Housing & Assembly

The fixture housing is fabricated from a combination of heavy duty extruded aluminum, cast aluminum, and spun aluminum. The Durban features toolless access to LED array and driver, allowing for quick and easy installation and maintenance.

LED

UNIVERSAL LED, UL listed LED modules and drivers, combined with a vertical heat sink and into one configurable unit which gives precise light distribution. It allows us to offer lumen adjustment on light output. These are 10CHIP, 500 LUMEN, 525 mA,,6v. 3.2watt per module, achieving 159 lumens per watt efficacy, 82CRI at 4000K. Beside maximizing heat dissipation surface, we also utilize convection-based heat management which creates additional air flow around the strips. Unlike a big metal heat sink where the temperature for the chips in the middle is higher than the rest, the heat of each of our modules gets dissipated evenly. This innovative heat dissipation design keeps the junction temperature low and ultimately prolongs the life of the LED strips. Our modules are covered by our standard 5-year warranty and are available in many of our fixture's designs. The drivers are dimmable 0-10v.

Also available with CFL option. Contact factory for more information.

Lens

Lens is fabricated from acrylic. Specify frosted or opal.

Mounting Options

Mounting kit containing (4) 5/8" dia. galvanized anchor bolts, (2) nuts & washers per bolt, included.

Finish

Thermoset polyester oven-baked powder coat in any standard color. Custom colors are available to your specification.

Certificates & Warranty

- ETL
- Suitable for Wet Locations
- 5-Year Warranty

Dimensions



