



**ZUMALIGHTING**  
QUALITY OUTDOOR SOLUTIONS



MODEL  
**NORCROSS**

TYPE  
**LED**

SERIES  
**SITE & AREA**

**ZUMA LIGHTING LLC**  
325 N LARCHMONT BLVD STE 406, LOS ANGELES, CA 90004  
[INFO@ZUMALIGHTING.COM](mailto:INFO@ZUMALIGHTING.COM) • (310) 975-3126 • [ZUMALIGHTING.COM](http://ZUMALIGHTING.COM)

# ORDERING INFORMATION

**Model NORCROSS**

**Type LED**

**Series SITE & AREA**



**NRC-PA**



**NRC-PT**

FIXTURE	WATTAGE / LUMENS	VOLTS	TEMP (KELVIN)	OPTICS	MOUNTING	COLOR	OPTIONS
NRC = Norcross	40W = 5,200lm  60W = 7,800lm  80W = 10,440lm  100W = 13,400lm  120W = 15,600lm  150W = 19,500lm  AW1 = Adjustable 40w-60w-80w  AW2 = Adjustable 100w-120w-150w	U = 120v-277v  MV = 120v - 347v  HV = 347v - 480v	3K = 3000K, 80 CRI  4K = 4000K, 80 CRI  5K = 5000K, 80 CRI  ACT* = 4000-5000K, 70 CRI  <i>*only available w/ AW1 or AW2</i>	T3 = Type III  T5 = Type V	PT = Post Top, fits over 3"OD (Double Arm)  PA= Bracket Arm, mounts to round / square pole (Single Arm)  WM = Wall Mount	DB = Dark Bronze  BK = Black  WH = White  NA = Natural Aluminum  CC = Custom	M = Motion Sensor  PC = Photocell  D = Dimming (0-10v)  SP10 = Surge Protection 10kV  SP20 = Surge Protection 20kV  MGF = Marine Grade Finish  HSS = House-side shield  EM = Emergency Battery Backup  WG = Wire Guard

# SPECIFICATIONS

## Housing

Die cast aluminum housing. Universal design accepts a variety of mounting arms for various applications.

## Electrical Components

High performance LEDs utilize state-of-the-art technologies for improved thermal performance. Available in Types III & V with wide choice of color temperatures ranging from CCT(3000K – 5000K). Power input 120-277v / 120-347v (347v – 480v optional).

Fixture can be specified with AW1 / AW2 for adjustable lumen output. Also available with ACT for adjustable CCT color temperature.

## Finish

Thermoset polyester oven-baked powder coat, in any standard color. Custom colors are available to your specification. Marine grade finish available upon request.

## Certificates & Warranty

- ETL Listed
- CSA
- RHSA Compliant
- DLC5.1 Premium
- Suitable for Wet Locations
- 5-Year Warranty

## Mounting

Fixture can be installed on post-top.

Tenon top mounting options:

- over 3" OD (standard)

Fixture can also be installed on mounting arms, sold separately. See architectural arm .pdf for style options.

