



MODEL WASHBURN

TYPE **LED**

SERIES ARCHITECTURAL







ZUMA LIGHTING LLC




ORDERING INFORMATION

Model WASHBURN

Type LED

Series ARCHITECTURAL



FIXTURE	WATTAGE	VOLTS	COLOR TEMP	OPTICS	SHADE SIZE	MOUNT	COLOR	OPTIONS
WAS =	10W	U = 120v-277v	27K = 2700K	T2 = Type II	18 = 18" dia.	AM = Arm	BZ8 =	M = Motion Sensor
Washburn	20W 30W 40W 60W 80W 90W 120W 150W 160W 200W 240W 300W* 340W* 360W*	8 = 480v	3K = 3000K 35K = 3500K 4K = 4000K 45K = 4500K 5K = 5000K	T3 = Type III T4 = Type IV T5 = Type V	24 = 24.5" dia. 30 = 30" dia.	Mount* WM = Wall Mount *Arm ordered separately	Zuma Bronze BK = GT Black WH = Alpine White SL = Iridium Silver GRY = Granite Gray GRN = Moss Green CC = Custom Specify RAL	PC = Photocell D = Dimming SP = Surge Protection HSS = Houseside Shield AGFL = Anti Glare Frosted Diffusion Lens* BAA = Buy American Act Compliant DSC = Dark Sky Compliant* *Only available with select optics, contact factory for details



SPECIFICATIONS

Housing

The Washburn fixture housing is constructed from a combination of heavy-duty cast and spun aluminum.

Electrical Components

High performance LEDs utilize state-of-the-art technologies for improved thermal performance. Available in Types II, III, IV, & V with wide choice of color temperatures ranging from CCT(2700K – 5000K). These LEDs are designed to fit LEDIL lenses with IP67 rating.

Lens

Optional anti-glare frosted diffusion lens is available is fabricated from acrylic.

Finish

Thermoset polyester oven-baked powder coat, in any standard color. Custom colors are available to your specification. Marine grade finish available upon request.

Certificates & Warranty

- Buy American Act (BAA) Compliant
- Dark Sky Compliant
- ETL
- Suitable for Wet Locations
- 5-Year Warranty

Mounting

Fixture can be installed on mounting arms, sold separately. See architectural arm .pdf for style options.

